





The MFlex Light System boasts an ergonomic design that ensures rapid installation and allows the lights to remain mounted even when the shelter is stored, thereby streamlining setup and deployment processes. The system features an integrated power supply and dimmer control, facilitating straightforward operation. Compared to traditional lighting systems, the MFlex significantly reduces shadowing, thereby enhancing operational effectiveness.

Engineered to endure demanding environments, the MFlex Light System offers exceptional reliability in military settings. Its lightweight construction and compatibility with the commonly used BB-2590/U NATO-approved battery make it particularly well-suited for field operations.

www.frontlinelighting.com

Standard

MFlex

int.sales@frontlinelighting.com



DESCRIPTION

Our advanced lighting solution is engineered to offer superior performance and versatility with a total weight of under 18 lbs (8.5 kg). It arrives pre-hung with hangers for effortless installation, ensuring a quick setup process. Designed to provide uniform light distribution without bright spots or a "Dazzle Effect," this system delivers exceptional brightness that outperforms competitive alternatives while maintaining a low heat signature. Manufactured in the USA, it operates using the NATO-approved BB-2590 battery, with the option to use a Frontline Battery Cable for added convenience. In medical applications, the blackout wavelength feature enables medical personnel to clearly differentiate between blood and other bodily fluids in low-light or blackout conditions.

MFLEX KIT BAG

- Made from Water resistant and Rugged Cordura
- Incorporated control box and power supply
- Molle and Velcro attachment system
- Internal component pouch

MFLEX LIGHT

- 40ft / 12m Length of White light, 240LED's p/m
- 40ft / 12m Length of Blackout light, 240LED's p/m
- Built to IP67 Standards
- Patented technology reduces voltage drop over extended lengths 12m < 10% drop

CONTROL BOX

- Toggle between white and blackout lighting
- Control box securely mounted inside bag

HEAVY DUTY CABLE

- Custom moulded connections with incorporated seal-locking system
- IP67 rated components
- 20ft / 6m cable length to light
- Double insulated



	SPECIFICATIONS	MFLEX - 12M	MFLEX - 18M	KIT CONTENTS:
	VOLTAGE	24VDC	24VDC	WHITE/BLACKOUT WHITE
	AMPERAGE - WHITE	3.5A	4A	Kit Bag • •
	AMERAGE - BLACKOUT	0.5A	2A	Power Supply
	LUMENS - WHITE	10660 LM	10660 LM	Control Box
	LUMENS - BLACKOUT	2518.67 LM	2518.67 LM	White Light
	LENGTH OF LIGHT STRIP	12M / 40 FT	18M / 60 FT	Blackout Light
	ССТ	4200K	4200K	Mounting Kit
	CRI	94	94	Velcro Straps
	OPERATING TEMP			Hanging Clips
	Fahrenheit (UL 62)	-40° - 120°	-40° - 120°	DC battery cable Optional Optional
	Celsius (UL 62)	-40° - 71°	-40° - 71°	De battery cable optional optional
	STORAGE			PHYSICAL SPECIFICATIONS:
	Fahrenheit	-50° - 160°	-50° - 160°	MFLex-12M Weight 15lb / 6.8kg MFLex - 18M Weight 18Lb / 8.2kg Bag Dimensions (in) 11.8 x 15.7 x 4.7
	Celsius	-45° - 71°	-45° - 71°	
	LIFETIME (Hrs)	50,000HRS	50,000HRS	
	WARRANTY	1 YEAR	1 YEAR	Bag Dimensions (m) $11.0 \times 13.7 \times 4.7$ Bag Dimensions (mm) $300 \times 400 \times 120$
	Tasting conducted at LIC Army Co	mbat Canabilitian Day	alanmant Command	Bug Bintensions (min) 300 x 100 x 120

Testing conducted at US Army Combat Capabilities Development Command Soldier Center, Natick Massachusetts